

A30

ONE-MAN POST HOLE AUGER

- ▶ **LOW WEIGHT**
- ▶ **EASY STARTING - EASY SERVICE**
- ▶ **HEAVY DUTY CLUTCH**
- ▶ **GEARED HIGH RATIO TRANS**

- Durable hardened steel gear transmission
- Large diameter HD clutch
- Simple starting 2 cycle Tecumseh engine
- Large 24 oz. fuel tank
- Engine parts widely available
- Full 360° rubber gripped handle
- Internal safety throttle with kill switch
- Shear pin with clevis auger attachment
- High fuel efficiency
- Uses regular gasoline and 2 cycle mix lubrication
- Modular design for easy service
- 1" diameter drive shaft
- Uses either standard 2, 4, 6, 8" diameter augers
- Available 6 and 8" diameter P Augers



Dimensions: 20x11x15" (no bit)

Clutch: Centrifugal 3.5"

Tank Size: 1.5 Qt.

Output Shaft: 1"

Starter: Recoil

Weight: 30 lbs (no bit)

Hp: 3.0 @ 4300 Rpm

Fuel: 24:1 2 Cycle oil

Engine max: 4700 Rpm

Auger max speed: 260 Rpm

Engine: 2 Cycle

Displacement: 85 cc

Carburation: Diaphragm

Air Filter: Foam

Max drill depth: 4'

SKIDRIL

P.O. Box 8041
Greensboro, NC 27419
Tel: 800-843-3745 Fax: 336-674-6690

