

HYDRAULIC POST DRIVER

- **ULTRA LIGHT**
- **WEIGHS LESS THAN 30 POUNDS**
- ONE MAIN MOVING PART
- TRIGGER VALVE FOR SILT FENCE
- · Low weight high impact force
- Uses Light weight 3/8" hoses
- · Super compact design
- Patented accumulator reduces recoil, adds power
- · Near perfect center of gravity
- · Self lubrication prevents damage
- Quiet closed circuit hydraulics creates no exhaust
- Requires only 5.5 GPM to run
- Drives T-Post, silt fence
- Drives stakes, rods and pins
- Can be powered by skid loader, tractor (and more) auxiliary circuits.
- 1 year warranty



Dimensions: 18X6" W/ Head Weight: 22 lbs Imact Rate: 1200-2000 Bpm

Flow: 5.5-7 GPM Pressure: 1600 PSI Impact Energy: 29 Ft-lb







HYDRAULIC T POST DRIVER

- ULTRA LIGHT
- **WEIGHS LESS THAN 40 POUNDS**
- ONE MAIN MOVING PART
- **DUAL ACTIVATION MODES**
- Low weight high impact force
- Uses Light weight 3/8" hoses
- Ribbed side handles offer excellent grip
- Patented accumulator reduces recoil, adds power
- Flat for T post or stakes
- Near perfect center of gravity
- Highest hitting force per pound of tool
- Optional inline valve for full length post driving
- Self lubrication prevents damage
- Quiet closed circuit hydraulics creates no exhaust
- Spring loaded valve activated from side handle
- Drives T-Post, rounds
- Drives stakes, rods and pins
- Runs off of skid steer loaders and tractors
- 1 year warranty



Dimensions: 17.5X10" W/O Head Weight: 37 lbs Imact Rate: 1200 Bpm

Flow: 5.5-7 GPM Pressure: 1600 PSI Impact Energy: 50 Ft-lb







HYDRAULIC POST DRIVER

- **ULTRA HEAVY DUTY**
- **WEIGHS LESS THAN 50 POUNDS**
- ONE MAIN MOVING PART
- **DUAL ACTIVATION MODES**
 - Low weight high impact force
 - Uses Light weight 3/8" hoses
 - Ribbed side handles offer excellent grip
 - Patented accumulator reduces recoil, adds power
- Two anvil options for tube or stakes
- Near perfect center of gravity
- Highest hitting force per pound of tool
- Optional inline valve for full length post driving
- Self lubrication prevents damage
- Quiet closed circuit hydraulics creates no exhaust
- Spring loaded valve activated from side handle
- Drives T-Post, rounds and sign posts of all types
- Drives stakes, rods and pins
- Runs off of skid steer loaders and tractors
- 1 year warranty



Dimensions: 22X10" W/O Head Weight: 46 lbs Imact Rate: 1200 Bpm

Flow: 5.5-7 GPM Pressure: 1600 PSI Impact Energy: 82 Ft-lb







HYDRAULIC POST DRIVER

- ULTRA HEAVY DUTY
- **WEIGHS LESS THAN 70 POUNDS**
- ONE MAIN MOVING PART
- **DUAL ACTIVATION MODES**
 - High impact force
- Uses Light weight 3/8" hoses
- Dual operating modes (remote or side handle)
- Ribbed side handles offer excellent grip
- Patented accumulator reduces recoil, adds power
- Two anvil options for tube or stakes
- Near perfect center of gravity
- Highest hitting force per pound of tool
- Optional inline valve for full length post driving
- Self lubrication prevents damage
- · Quiet closed circuit hydraulics creates no exhaust
- Spring loaded valve activated from side handle
- Drives up to 4" posts of all types
- Drives stakes, rods and pins
- Runs off of skid steer loaders



Remote Valve



Flow: 5.5-8 GPM Pressure: 1600 PSI Impact Energy: 92 Ft-lb







AIR POWERED POST DRIVER

- ULTRA HEAVY DUTY
- **WEIGHS LESS THAN 40 POUNDS!**
- ONE MAIN MOVING PART
- **QUICK CHANGE DRIVE CAPS**
 - Low weight high impact force
- Uses Light weight 1/2" hose
- Ribbed side handles offer excellent grip
- Low air consumption reduces compressor size
- · Two anvil options for tube or stakes
- Near perfect center of gravity
- · Highest hitting force per pound
- Does not require a bulky inline lubricator
- Muffled air exhaust reduces noise level
- Spring loaded valve activated from side handles
- Drives T-Post, rounds and sign posts of all types
- Drives stakes, rods and pins
- 1 year warranty
- Pat. Pending



Dimensions: 22X10" W/O Head Weight: 38 lbs Imact Rate: 1200 Bpm
Air flow: 17-65 Cfm Air Pressure: 100-145 PSI Impact Energy: 50 Ft-lb



